

WHAT IS CLAIMED IS:

1. A decoding apparatus configured to decode
compression-encoded video data in units of at least one
block, the video data including a variable length code
5 comprising:

a variable length decoder which decodes the
variable length code to output a zero-run length and
a nonzero coefficient;

an inverse quantizer which inverse-quantizes the
10 nonzero coefficient to output an inverse-quantized
result;

a zero-run reconstruction processor which
reconstruct zero coefficients, the zero coefficients
corresponding to the zero-run length;

15 a FIFO (First-In First-Out) memory arranged
between the inverse quantizer and the zero-run
reconstruction processor and configured to store the
zero-run length data and nonzero coefficients, the
memory operating with first-in first-out and having
20 a memory capacity for storing coefficients contained in
a plurality of blocks;

an inverse discrete cosine transformer which
subjects the reconstructed coefficients and inverse-
quantized coefficient to an inverse discrete cosine
25 transformation to output a transformed result; and

a motion compensator which subjects the
transformed result to a motion compensation.

2. An apparatus according to claim 1, wherein the variable length decoder decodes the variable length code corresponding to a macro block including the given number of blocks.

5 3. An apparatus according to claim 1, wherein the zero-run reconstruction device includes a buffer memory configured to write in the zero coefficients and nonzero coefficients therein at a write-in speed and read out them therefrom at a readout speed higher than
10 the write-in speed.

 4. An apparatus according to claim 1, wherein if nonzero coefficient does not exist at a final position of a block when the inverse quantizer receives a block end signal indicating the end of the block from the
15 variable length decoder, the inverse quantizer generates a zero coefficient as the final DCT coefficient of the block.

 5. An apparatus according to claim 1, wherein the variable length decoder stops its output in units of
20 one block when the inverse quantizer is unreceivable the zero-run length and nonzero coefficient from the variable length decoder.

 6. An apparatus according to claim 1, wherein every time the inverse quantizer receives the zero-run
25 length from the variable length decoder, the inverse quantizer accumulates a value obtained by adding "1" to the zero-run length and generates scan address data

indicating a coefficient position of the nonzero coefficient, to generate quantization step size data every coefficient position based on the scan address data and scan pattern data indicating the scan pattern.

5 7. An apparatus according to claim 6, wherein the inverse quantizer outputs to the first-in first-out memory DCT coefficient data indicating the inverse quantization result, the scan address data indicating a position of the DCT coefficient and the scan pattern data.

10 8. An apparatus according to claim 7, wherein the inverse quantizer stops its output in units of one coefficient when the FIFO memory is unreceivable the data from the inverse quantizer.

15 9. An apparatus according to claim 1, wherein the zero-run reconstruction processor includes an internal scan address counter increased one by one for each clock, and rejects next data input from the FIFO memory until a scan address received from the FIFO memory has coincided with a count value of the internal scan address counter, to generate the zero coefficients corresponding to the zero-run length.

20 10. An apparatus according to claim 3, wherein when the buffer memory writes in 58 to 62 percents of all coefficients corresponding to one block, the buffer memory reads out the coefficients.

25 11. An apparatus according to claim 1, which

00942507.093101
107660 20924660

includes an intra-DC reconstruction device configured to reproduce DC components contained in the coefficients in intra-blocks in parallel with inverse quantization of the inverse quantizer.

- 5 12. A decoding apparatus configured to decode compression-encoded video data including a variable length code, comprising:

 a plurality of decompression devices configured to decompress compression-encoded video data corresponding to a plurality of channels, respectively, each of the decompression devices including:

10

 a variable length decoder which decodes the variable length code to output a zero-run length and a nonzero coefficient;

- 15 an inverse quantizer which inverse-quantizes the nonzero coefficient to output an inverse-quantized result;

 a zero-run reconstruction processor which reconstruct zero coefficients corresponding to the zero-run length; and

20

 a FIFO (First-In First-Out) memory arranged between the inverse quantizer and the zero-run reconstruction processor and configured to store the zero-run length data and nonzero coefficients, the memory operating with first-in first-out and having a memory capacity for storing coefficients contained in a plurality of blocks;

25

a plurality of parameter extractors provided
corresponding to the decoding processors, and
configured to generate parameters concerning one macro-
block every time the variable length decoder included
5 in each of the decoding processors completes decoding
of one block; and

an inverse discrete cosine transformer which
subjects the coefficients from the decoding processors
to inverse discrete cosine transformation to obtain
10 transformed coefficients; and

a motion compensator which subjects the
transformed coefficients to a motion compensation in
accordance with the parameters concerning one block
input from the parameter extractors alternately.

13. An apparatus according to claim 12, wherein
15 the variable length decoder decodes the variable
length code corresponding to a macro block including
a predetermined number of blocks.

14. An apparatus according to claim 12, wherein
20 the zero-run reconstruction device includes a buffer
memory configured to write in the zero coefficients and
nonzero coefficients therein at a write-in speed and
read out them therefrom at a readout speed higher than
the write-in speed.

15. An apparatus according to claim 12, wherein if
25 nonzero coefficient does not exist at a final position
of a block when the inverse quantizer receives a block

0942607 083404
TOP SECRET 20527660

end signal indicating the end of the block from the variable length decoder, the inverse quantizer generates a zero coefficient as the final DCT coefficient of the block.

5 16. An apparatus according to claim 12, wherein the variable length decoder stops its output in units of one coefficient when the inverse quantizer is unreceivable the zero-run length and nonzero coefficient from the variable length decoder.

10 17. An apparatus according to claim 12, wherein every time the inverse quantizer receives the zero-run length from the variable length decoder, the inverse quantizer accumulates a value obtained by adding "1" to the zero-run length and generates scan address data
15 indicating a coefficient position of the nonzero coefficient, to generate quantization step size data every coefficient position based on the scan address data and scan pattern data indicating the scan pattern.

20 18. An apparatus according to claim 12, wherein the zero-run reconstruction processor includes an internal scan address counter increased one by one for each clock, and rejects next data input from the FIFO memory until a scan address received from the FIFO
25 memory has coincided with a count value of the internal scan address counter, to generate the zero coefficients corresponding to the zero-run length.

19. An apparatus according to claim 12, which

00042507 083101

includes an intra-DC reconstruction device configured to reproduce DC components contained in the coefficients in intra-blocks in parallel with inverse quantization of the inverse quantizer.

101230 402400